

Product Guide

Ordering Information					Outlet Spacing (in)	Flow Rates					
Tape Size Diameter		Spacing Code (in)	Flow Code	*Custom Flow		Q / 100 ft				Emitter	
5 = 5/8"	7 = 7/8"					GPM		GPH		GPH	
xx = mil Wall Thickness						8 psi	10 psi	8 psi	10 psi	8 psi	10 psi
05, 06, 08, 10, 12, 15	05, 06, 08, 10, 12, 15										
5xx-06-200	7xx-06-200	06	200		6	0.20	0.23	12	14	0.06	0.07
5xx-12-100	7xx-12-100	12	100		12	0.10	0.12	6	7		
5xx-18-070	7xx-18-070	18	070		18	0.07	0.08	4	5		
5xx-24-050	7xx-24-050	24	050		24	0.05	0.06	3	4		
5xx-06-230	7xx-06-230	06	230		6	0.23	0.26	14	16	0.07	0.08
5xx-12-120	7xx-12-120	12	120		12	0.12	0.13	7	8		
5xx-18-080	7xx-18-080	18	080		18	0.08	0.09	5	5		
5xx-24-060	7xx-24-060	24	060		24	0.06	0.07	4	4		
5xx-06-260	7xx-06-260	06	260	*	6	0.26	0.29	15.6	17.4	0.078	0.087
5xx-04-450	7xx-04-450	04	450		4	0.45	0.50	27	30	0.09	0.10
5xx-08-230	7xx-08-230	08	230		8	0.23	0.25	14	15		
5xx-12-150	7xx-12-150	12	150		12	0.15	0.17	9	10.2		
5xx-16-110	7xx-16-110	16	110		16	0.11	0.125	7	7.5		
5xx-24-110	7xx-24-110	24	075		24	0.075	0.083	4.5	5		
5xx-04-500	7xx-04-500	04	500		4	0.50	0.56	30	34	0.10	0.112
5xx-08-250	7xx-08-250	08	250		8	0.25	0.28	15	17		
5xx-12-170	7xx-12-170	12	170		12	0.17	0.19	10	11		
5xx-16-130	7xx-16-130	16	130		16	0.13	0.14	8	8		
5xx-24-080	7xx-24-080	24	080		24	0.08	0.09	5	5		
5xx-04-670	7xx-04-670	04	670		4	0.67	0.75	40	45	0.13	0.15
5xx-08-340	7xx-08-340	08	340		8	0.34	0.37	20	22		
5xx-12-220	7xx-12-220	12	220		12	0.22	0.25	13	15		
5xx-16-170	7xx-16-170	16	170		16	0.17	0.19	10	11		
5xx-24-110	7xx-24-110	24	110		24	0.11	0.12	7	7		
5xx-04-1.00	7xx-04-1.00	04	1.00		4	1.05	1.15	63	69	0.21	0.23
5xx-08-500	7xx-08-500	08	500		8	0.52	0.57	31	34		
5xx-12-350	7xx-12-350	12	350		12	0.35	0.38	21	23		
5xx-16-260	7xx-16-260	16	260		16	0.26	0.29	16	17		
5xx-24-170	7xx-24-170	24	170		24	0.17	0.19	10	11		
5xx-04-1.34	7xx-04-1.34	04	1.34		4	1.34	1.50	80	90	0.27	0.30
5xx-08-670	7xx-08-670	08	670		8	0.67	0.75	40	45		
5xx-12-450	7xx-12-450	12	450		12	0.45	0.50	27	30		
5xx-16-340	7xx-16-340	16	340		16	0.34	0.37	20	22		
5xx-24-220	7xx-24-220	24	220		24	0.22	0.25	13	15		

* Custom Flows Available

$$C_v \leq 0.03 \quad \text{Emitter Exponent} = 0.5$$